NOTE: WHERE TRENCH PASSES THROUGH EXISTING PAVEMENT
THE PAVEMENT SHALL BE CUT ALONG A NEAT VERTICAL LINE
12" FROM THE A/C CUT AT THE EDGE OF THE TRENCH OPENING
AFTER RESTORATION OF THE TRENCH BACKFILL.

A/C CUT FOR PAVEMENT REPLACEMENT A/C CUT FOR TRENCH EXCAVATION SUBGRADE OR GROUND SURFACE TRENCH MATERIAL -MIN. 24' BACKSLOPE TO CONFORM TO 0.S.H.A. **REGULATIONS** TRENCH BACKFILL (AS SPECIFIED) TRENCH WIDTH BEDDING MATERIAL PLACED IN 6" LIFTS AND COMPACTED TO 95% PER AASHTO T-99, OR AS SPECIFIED PIPE BEDDING -WHERE REQUIRED FOR SOFT

NOTE: WHEN IN UNSTABLE OR SOFT MATERIAL, TRENCH WALLS
SHALL BE BACKSLOPED FROM THE BOTTOM OF THE TRENCH

TYPICAL TYPE 1 TRENCH DETAIL

PIPE O.D.+2' MIN. WIDTH 3.5'

OFFICE OF CITY ENGINEER GREAT FALLS, MONTANA

OR UNSTABLE FOUNDATION

NOVEMBER 1987 REVISED

5 - 30